

SAC-350/450/550

Automatic Turret Rewinder

FEATURES

- Equipped with one unloading system
- Simple ergonomic design
- Taper tension rewinding function
- Servo controlled with 100% paper splicing success rate
- Stable tension control system, with unique tension coupling method
- Easy connection to main machine without cables

OPTIONS

- 850mm diameter
- Slitting device
- Max speed 250m/min

MATERIALS RANGE

- Paper : 60gsm-400gsm
- Plastic film: > 25um
- ABL/BPL tube laminated

TECHNICAL SPECIFICATIONS

Model	SAC-350	SAC-450	SAC-550
Max Web Width	350mm	450mm	550mm
Max.rewinding Diameter	680mm	680mm	680mm
Max.run Speed	180m/min	180m/min	180m/min
Unwind Tension Precision	±2%	±2%	±2%
Paper Splicing Method	Automatic pre-speed splicer	Automatic pre-speed splicer	Automatic pre-speed splicer
Unloading	Manual unloading part	Manual unloading part	Manual unloading part
Paper Core Alignment	Laser positioning	Laser positioning	Laser positioning
Total Power	5kw	6.8kw	6.8kw
Voltage	380V/50hz, 3phase	380V/50hz, 3phase	380V/50hz, 3phase
Machine Weight	1400kgs	1500kgs	1600kgs
Machine Size (LxWxH)	1700x1000x1500mm	1700x1100x1500mm	1700x1200x1500mm

Note: All technical parameters are subject to change without notice.

